



Flat Wire Molded Inductor
 Size 7020




- Composite core material allows high saturation currents
 - Very low acoustic noise and very low leakage flux noise
 - High inductance capability and handles high transient currents
 - C-Q200 qualified
 - Operating temperature -55 to +155 °C (Including self-temperature rise)
 - Quantity: 2000pcs
- DC/DC converters for entertainment/navigation systems
 - Applications: windshield power mirrors / heating and ventilation blowers / HID lighting
 - LED driver

Dimensions: [mm]



Land Pattern: [mm]




Electrical Properties:

Saturation Current will cause L to drop approximately 30%

Temperature Rise Current that causes the specified temperature rise from 25°C ambient.

Soldering Reflow:



Preheat condition: 150 ~200 °C / 60~120 sec.

Allowed time above 217 °C : 60~90 sec.


Max temperature: 260 °C .

Max time at max temperature: 10 sec.

Allowed Reflow time: 2x max.


Packaging Information:

Tape Dimension :



Series	A0 (mm)	B0 (mm)	D (mm)	P0 (mm)	P1 (mm)	W (mm)	K0 (mm)	E (mm)	T (mm)
MDTA7020	8.2±0.1	8.0±0.1	1.5±0.1	4.0±0.1	12.0±0.1	16.0±0.3	2.3±0.1	1.75±0.1	0.35±0.05

Peel force of top cover tape:




The peel force of top cover tape shall be between 0.1 to 1.3 N

Product Marking:

Marking	Printing (Inductance)
---------	-----------------------

Reel Dimension: [mm]



Packaging Quantity: